
FP3000-VESA

Flat-Panel VESA Mount Display for Honeywell Classic Universal or Z-Style Stations

*LED backlit display
with Infrared Touchscreen*



A High Quality Replacement Display

The FP3000-VESA is an LED-Backlit flat panel display designed to be a replacement for the Honeywell VESA "Bolt On" monitor utilizing the EPDG/EPDGP video system. Easy installation with VESA mount allows technician to use exiting cables for video/touchscreen, new power adaptor included.

Integrated Infrared Touch Screen

Honeywell's Universal Stations originally used infrared touch screen technology, which is reliable, provides dependable picks, and requires no finger pressure. This technology has the advantage of requiring no additional layer on the glass, resulting in a sharp, high-contrast display. For these reasons, infrared touch screens are preferred by many operators. The FP3000-VESA is offered with infrared touch screen, providing the performance and benefits of this original technology. Touchscreen connection either 9-pin Serial or USB.

Brilliant Image Quality

The FP3000-VESA factory settings yield an exceptional image quality for a typical US with EPDG/EPDGP video. In a side-by-side comparison with Honeywell's solution, users notice a much sharper image. The brightness, contrast, and black level values can be adjusted for your particular environment and preference.

Low Maintenance

The FP3000-VESA requires low maintenance just periodic cleaning of the glass faceplate. This faceplate has an anti-glare coating, use only a residue-free glass cleaner with a non-abrasive lint-free cloth.

Specifications

Viewable Area: 19" diagonal (14.81" x 11.85")

Physical Area: 14"height x 17.75"wide x 3.5"depth

Viewing Angle: 170° horizontal, 170° vertical

Power Consumption: 30 watts, 110VAC/240VAC

Display modes supported: VGA 640x480 through VESA 1280x1024, includes EPDG scan frequency. 15-pin connector, 9-15-pin adapter included.

Brightness: 300 cd/m²

Operating Environment: Temperature 0-50°C, Relative Humidity < 90% at < 40°C

Weight: 8.8 kg, 19.38 lb



WESTERN PROCESS COMPUTERS, INC.
2033 W. NORTH LANE, SUITE 14
PHOENIX, AZ 85021

Phone: 602-997-7245
Fax: 602-997-7248
info@westernprocess.com
www.westernprocess.com